



Link-Layer Contention

EE 122: Intro to Communication Networks

Fall 2007 (WF 4-5:30 in Cory 277)

Vern Paxson

TAs: Lisa Fowler, Daniel Killebrew & Jorge Ortiz

<http://inst.eecs.berkeley.edu/~ee122/>

Materials with thanks to Jennifer Rexford, Ion Stoica, and colleagues at Princeton and UC Berkeley

1

Our Story So Far


- Single shared broadcast channel
 - Avoid having multiple nodes speaking at once
 - Otherwise, collisions lead to garbled data
- Multiple access mechanism
 - Distributed algorithm for sharing the channel
 - Algorithm determines which node can transmit
- Classes of techniques
 - **Channel partitioning**: divide channel into pieces
 - o TDMA and FDMA (time-division & frequency-division)
 - **Taking turns**: scheme for trading off who gets to transmit
 - **Random access**: allow collisions, and then recover
 - o Optimizes for the common case of only one sender

2

“Taking Turns” MAC protocols

Polling

- Master node “invites” slave nodes to transmit in turn




- Concerns:
 - Polling overhead
 - Latency
 - Single point of failure (master)

Token passing

- Control token passed from one node to next sequentially

- Node must have token to send

- Concerns:
 - Token overhead
 - Latency
 - Single point of failure (token)



3

Random Access Protocols


- When node has packet to send
 - Transmit at full channel data rate
 - No *a priori* coordination among nodes
- Two or more transmitting nodes \Rightarrow collision
 - Data lost
- Random access MAC protocol specifies:
 - How to detect collisions
 - How to recover from collisions
- Examples
 - ALOHA and Slotted ALOHA
 - CSMA, CSMA/CD, CSMA/CA

4

Slotted ALOHA

Assumptions

- All frames same size
- Time divided into equal slots (time to transmit a frame)
- Nodes are synchronized
- Nodes begin to transmit frames *only at start of slots*
 - No carrier sense
- If two or more nodes transmit, all nodes detect collision




Operation

- When node obtains fresh frame, transmits in next slot
- No collision: node can send new frame in next slot
- Collision: node retransmits frame in each subsequent slot with probability p until success

5

Slotted ALOHA



Pros

- Single active node can continuously transmit at full rate of channel
- Highly decentralized: only slots in nodes need to be in sync
- Simple

Cons

- Collisions, wasting slots
- Idle slots
- Nodes may be able to detect collision in less than time to transmit packet
- Clock synchronization

6

Slotted Aloha efficiency

Efficiency: long-run fraction of successful slots (many nodes, all with many frames to send)

• *Suppose*: N nodes with many frames to send, each transmits in slot with probability p

• Probability that given node has success in a slot = $p(1-p)^{N-1}$

• Probability that *any* node has a success = $Np(1-p)^{N-1}$

- Maximum efficiency: find p^* that maximizes $Np(1-p)^{N-1}$
- For many nodes, take limit of $Np^*(1-p^*)^{N-1}$ as N goes to infinity, gives:

Maximum efficiency = $1/e \approx .37$

At best: under heavy load, channel wasted 63% of the time!

Can also show that without slots, efficiency drops to $1/(2e) \approx .18$

7