

# HW 0: Executable

CS 162

Due: September 7, 2015

## Contents

<b>1</b>	<b>Setup</b>	<b>2</b>
1.1	GitHub . . . . .	2
1.2	Instructional account . . . . .	2
1.3	Vagrant . . . . .	2
1.3.1	Windows . . . . .	3
1.3.2	ssh-keys . . . . .	3
1.3.3	Repos . . . . .	3
1.4	Autograder . . . . .	4
1.5	Editing code in your VM . . . . .	4
1.5.1	Windows . . . . .	5
1.5.2	Mac OS X . . . . .	5
1.5.3	Linux . . . . .	5
1.6	Shared Folders . . . . .	5
<b>2</b>	<b>Useful Tools</b>	<b>6</b>
2.1	git . . . . .	6
2.2	make . . . . .	6
2.3	gdb . . . . .	7
2.4	tmux . . . . .	7
2.5	vim . . . . .	7
<b>3</b>	<b>Your first assignment</b>	<b>8</b>
3.1	make . . . . .	8
3.2	wc . . . . .	8
3.3	Executables and addresses . . . . .	8
3.4	user limits . . . . .	9
3.5	Autograder & Submission . . . . .	10

This semester, you will be using various tools in order to submit, build, and debug your code. This assignment is designed to help you get up to speed on some of these tools.

**This assignment is due 11:59 pm 9/7/2015**

## 1 Setup

### 1.1 GitHub

Code submission for all projects and homework in the class will be handled via GitHub so you will need a GitHub account. We will provide you with private repositories for all your projects. **You must not use your own public repositories for storing your code.** Visit [cs162.eecs.berkeley.edu/autograder](https://cs162.eecs.berkeley.edu/autograder)<sup>1</sup> to register with the autograder.

### 1.2 Instructional account

Once you register your GitHub account with our autograder, you will receive an instructional account form via email. You will not need this instructional account for this course, but it will give you access to campus computing resources that may be useful.

### 1.3 Vagrant

We have prepared a Vagrant virtual machine image that is preconfigured with all the tools necessary to run and test your code for this class. Vagrant is a tool for managing virtual machines. You can use Vagrant to download and run the virtual machine image we have prepared for this course.

Note: If you do not want to set up Vagrant on your own machine, you can use any of the instructional machines for this homework. For future assignments, you can use icluster24.eecs to run Pintos, but this machine will be significantly slower than developing locally.

**(If you are using Windows, these steps might not work – skip to the section below labeled “Windows”)**

1. Vagrant depends on VirtualBox (an open source virtualization product) so first you will need to download and install the appropriate version from the [VirtualBox website](https://www.virtualbox.org/wiki/Downloads)<sup>2</sup>. We will talk in class about virtual machines, but you can think of it as a software version of actual hardware.
2. Now install the appropriate version of Vagrant from the [Vagrant website](http://www.vagrantup.com/downloads.html)<sup>3</sup> (78 MB).
3. Once Vagrant is installed, type the following into your terminal:

```
mkdir cs162-vm
cd cs162-vm
vagrant init cs162/fall2015
vagrant up
vagrant ssh
```

These commands will download our virtual machine image from our server and start a ssh session. Note the “up” command will take a while, and requires an Internet connection.

4. You need to run all vagrant commands from the cs162-vm directory you created earlier. Do NOT delete that directory, or vagrant will not know how to manage the VM you created.

<sup>1</sup><https://cs162.eecs.berkeley.edu/autograder>

<sup>2</sup><https://www.virtualbox.org/wiki/Downloads>

<sup>3</sup><http://www.vagrantup.com/downloads.html>

5. You can run `vagrant halt` to stop the virtual machine. If this command does not work, make sure you are running it from your host machine, not inside SSH. To start the virtual machine the next time, you only need to run `vagrant up` and `vagrant ssh`. All of the other steps do not need to be repeated.

### 1.3.1 Windows

Since windows does not support ssh, the “`vagrant ssh`” command from the above steps will cause an error message prompting you to download Cygwin or something similar that supports an ssh client. [Here](#)<sup>4</sup> is a good guide on setting up Vagrant with Cygwin in windows.

### 1.3.2 ssh-keys

You will need to setup your ssh keys in order to authenticate with GitHub from your VM.

#### New GitHub Users

SSH into your VM and run the following:

```
ssh-keygen -N "" -f ~/.ssh/id_rsa
cat ~/.ssh/id_rsa.pub
```

The first command created a new SSH keypair. The second command displayed the public key on your screen. You should log in to GitHub and go to [github.com/settings/ssh](https://github.com/settings/ssh)<sup>5</sup> to add this SSH public key to your GitHub account. The title of your SSH keypair can be “CS 162 VM”. The key should start with “ssh-rsa” and end with “vagrant@development”.

#### Experienced GitHub Users

If you already have a GitHub SSH keypair set up on your local machine, you can use your local ssh-agent to utilize your local credentials within the virtual machine via ssh agent forwarding. Simply use `vagrant ssh` to ssh into your machine. The Vagrant should enable SSH agent forwarding automatically. If this doesn’t work, you can also use the instructions in the previous “New GitHub Users” section.

### 1.3.3 Repos

You will have access to two private repositories in this course: a personal repository for homework, and a group repository for projects. We will publish skeleton code for homeworks in [Berkeley-CS162/ta](https://github.com/Berkeley-CS162/ta)<sup>6</sup> and we will publish skeleton code for group projects in [Berkeley-CS162/group0](https://github.com/Berkeley-CS162/group0)<sup>7</sup>. These two skeleton code repositories are already checked out in the home folder of your VM, inside `~/code/personal` and `~/code/group`.

You will use the “Remotes” feature of Git to pull code from our skeleton repos (when we release new skeleton code) and push code to your personal and group repos (when you submit code). The Git Remotes feature allows you to link GitHub repositories to your local Git repository. We have already set up a remote called “staff” that points to our skeleton code repos on GitHub, for both your personal and group repo. You will now add your own remote that points to your private repo so you can submit code.

You should have received the link to your personal private GitHub repo when you registered with the autograder earlier. Add a new remote by doing the following steps in your VM:

<sup>4</sup><https://gist.github.com/rogerhub/456ae31427aafe5b70f7>

<sup>5</sup><https://github.com/settings/ssh>

<sup>6</sup><https://github.com/Berkeley-CS162/ta/>

<sup>7</sup><https://github.com/Berkeley-CS162/group0/>

1. First cd into your personal repository

```
cd ~/code/personal
```

2. Then visit your personal repo on GitHub and find the SSH clone URL. It should have the form “git@github.com:Berkeley-CS162/...”
3. Now add the remote

```
git remote add personal YOUR_GITHUB_CLONE_URL
```

4. You can get information about the remote you just added

```
git remote -v  
git remote show personal
```

5. Pull the skeleton, make a test commit and push to `personal master`

```
git pull staff master  
touch test_file  
git add test_file  
git commit -m "Added a test file."  
git push personal master
```

In this course, “master” is the default Git branch that you will use to push code to the autograder. You can create and use other branches, but only the code on your master branch will be graded.

6. Within 30 minutes you should receive an email from the autograder. (If not, please notify the instructors via Piazza). Check [cs162.eecs.berkeley.edu/autograder](https://cs162.eecs.berkeley.edu/autograder)<sup>8</sup> for more information.

## 1.4 Autograder

Here are some important details about how the autograder works:

- The autograder will automatically grade code that you push to your master branch, UNLESS the assignment you are working on is LATE.
- If your assignment is late, you can still get it graded, but you will be using slip days. You can request late grading using the autograder’s web interface at [cs162.eecs.berkeley.edu/autograder](https://cs162.eecs.berkeley.edu/autograder)<sup>9</sup>.
- Your final score will be the best score that you received in any build. So, even if you push code that fails more autograder tests than before, it will not decrease your score.
- If your score does not improve when you push new code, it will not affect your slip days. So, if you request a build after the deadline that does not improve your score, you will not have to use slip days.

## 1.5 Editing code in your VM

The VM contains a SMB server that lets you edit files in the vagrant user’s home directory. With the SMB server, you can edit code using text editors on your host and run git commands from inside the VM. **This is the recommended way of working on code for this course**, but you are free to do whatever suits you best.

---

<sup>8</sup><https://cs162.eecs.berkeley.edu/autograder>

<sup>9</sup><https://cs162.eecs.berkeley.edu/autograder>

### 1.5.1 Windows

1. Open the file browser, and press **Ctrl L** to focus on the location bar.
2. Type in `\\192.168.162.162\vagrant` and press **Enter**.
3. The username is **vagrant** and the password is **vagrant**.

You should now be able to see the contents of the vagrant user's home directory.

### 1.5.2 Mac OS X

1. Open Finder.
2. In the menu bar, select **Go** → **Connect to Server...**
3. The server address is `smb://192.168.162.162/vagrant`.
4. The username is **vagrant** and the password is **vagrant**.

You should now be able to see the contents of the vagrant user's home directory.

### 1.5.3 Linux

Use any SMB client to connect to the `/vagrant` share on 192.168.162.162 with the username **vagrant** and password **vagrant**. Your distribution's file browser probably has support for SMB out of the box, so look online for instructions about how to use it.

## 1.6 Shared Folders

The `/vagrant` directory inside the virtual machine is connected to the home folder of your host machine. You can use this connection if you wish, but the SMB method in the previous section is recommended.

## 2 Useful Tools

Before continuing, we will take a brief break to introduce you to some useful tools that make a good fit in any system hacker's toolbox. Some of these (git, make) are MANDATORY to understand in that you won't be able to compile/submit your code without understanding how to use them. Others such as gdb or tmux are productivity boosters; one helps you find bugs and the other helps you multitask more effectively. All of these come pre-installed on the provided virtual machine.

**Note:** We do not go into much depth on how to use any of these tools in this document. Instead, we provide you links to resources where you can read about them. We highly encourage this reading even though not all of it is necessary for this assignment. We guarantee you that each of these will come in handy throughout the semester. If you need any additional help, feel free to bother any of the TA's at office hours!

### 2.1 git

git is a version control program that helps keep track of your code. Think of it as Dropbox (but optimized for code). GitHub is only one of the many services that provide a place to host your code. You can use git on your own computer, without GitHub, but pushing your code to GitHub lets you easily share it and collaborate with others.

At this point, you have already tried out the basics of git, to set up your repos. But an understanding the inner workings of git will help you on your hacking.

If you have never used git or want a fresh start, we recommend you start [here](#)<sup>10</sup>. If you sort of understand git, [this presentation](#)<sup>11</sup> we made and [this website](#)<sup>12</sup> will be useful in understanding the inner workings a bit more.

At this point, cd into hw0 and ls should show a couple of .c files.

### 2.2 make

make is a utility that automatically builds executable programs and libraries from source code by reading files called Makefiles, which specify how to derive the target program. How it does this is pretty cool: you list dependencies in your Makefile and make simply traverses the dependency graph to build everything. Unfortunately, make has very awkward syntax that is, at times, very confusing if you are not properly equipped to understand what is actually going on.

A few good tutorials are [here](#)<sup>13</sup> and [here](#)<sup>14</sup>. And of course the official GNU documentation (though it may be a bit dense) [here](#)<sup>15</sup>.

For now we will use the simplest form of make: without a `Makefile`. (But you will want to learn how to build decent Makefiles before long!) You can compile and link `wc.c` by simply running:

```
make wc
```

This created an executable, which you can run. Try

```
./wc wc.c
```

How is this different from the following?

```
wc wc.c
```

---

<sup>10</sup><http://git-scm.com/book/en/Getting-Started>

<sup>11</sup><http://goo.gl/cLBs3D>

<sup>12</sup><http://think-like-a-git.net/>

<sup>13</sup><http://wiki.wlug.org.nz/MakefileHowto>

<sup>14</sup><http://mrbook.org/blog/?s=make>

<sup>15</sup><http://www.gnu.org/software/make/manual/make.html>

Hint: `which wc`.

Your first assignment is going to be to modify `wc.c`, so that it implements word count according to `man wc`, except that it does not need to support any flags and only needs to support a single input file, (or `STDIN` if none is specified).

## 2.3 gdb

Debugging C programs is hard. Crashes don't give you nice exception messages or stack traces by default. Fortunately, there's `gdb`. If you compile your programs with a special flag `-g` then the output executable will have debug symbols, which allow `gdb` to do its magic. If you run your C program inside `gdb` it will allow you to not only look get a stack trace, but inspect variables, change variables, pause code and much more!

Normal `gdb` has a very plain interface. So, we have installed `cgdb` for you to use on the virtual machine, which has syntax highlighting and few other nice features. In `cgdb`, you can use `i` and `ESC` to switch between the two panes.

`gdb` can start new processes and attach to existing processes (which will be useful when debugging your project.)

[This](#)<sup>16</sup> is an excellent read on understanding how to use `gdb`.

Again, [the official documentation](#)<sup>17</sup> is also good, but a bit verbose.

Take a moment to begin working on your `wc`. Provide the `-g` flag when you compile your program with `gcc`. Start the program under `gdb`. Set a break point at `main`. Run to there. Try out various commands. Figure out how to pass command line arguments. Add local variables and try probing their values. Learn about `step`, `next`, and `break`.

## 2.4 tmux

`tmux` is a terminal multiplexer. It basically simulates having multiple terminal tabs, but displays them in one terminal session. It saves having to have multiple tabs of `ssh`ing into your virtual machine.

You can start a new session with `tmux new -s <session_name>`

Once you create a new session, you will just see a regular terminal. Pressing `ctrl-b + c` will create a new window. `ctrl-b + n` will jump to the `n`th window.

`ctrl-b + d` will “detach” you from your `tmux` session. Your session is still running, and so are any programs that you were running inside it. You can resume your session using `tmux attach -t <session_name>`. The best part is this works even if you quit your original `ssh` session, and connect using a new one.

[Here](#)<sup>18</sup> is a good `tmux` tutorial to help you get started.

## 2.5 vim

`vim` is a nice text editor to use in the terminal. It's well worth learning. [Here](#)<sup>19</sup> is a good series to get better at `vim`. Others may prefer `emacs`. Whichever editor you choose, you will need to get proficient with an editor that is well suited for writing code.

<sup>16</sup><http://www.unknownroad.com/rtfm/gdbtut/gdbtoc.html>

<sup>17</sup><https://sourceware.org/gdb/current/onlinedocs/gdb/>

<sup>18</sup><http://danielmiessler.com/study/tmux/>

<sup>19</sup><http://derekwyatt.org/vim/tutorials/>

### 3 Your first assignment

#### 3.1 make

You have probably been using `gcc` to compile your programs, but this grows tedious and complicated as the number of files you need to compile increases. You will need to write a `Makefile` that compiles `main.c`, `wc.c`, and `map.c` when `make` is run (you may want to add the `-g` gcc flag to this step). It may also help to write a clean target (for `make clean`) to remove your binaries. If all of this is new to you please read 2.2 make.

#### 3.2 wc

We are going to use `wc.c` to get you thinking once again in C, with an eye to how applications utilize the operating system - passing command line arguments from the shell, reading files, and standard file descriptors. All of these things you encountered in CS 61C, but they will take on new meaning in CS 162.

Your first task to write a clone of the unix tool `wc`, which counts the number of lines, words, and characters inside a particular text file. You can run unix's `wc` to see what your output should look like, and try to mimic its basic functionality in `wc.c` (don't worry about the flags or spacing in the output).

You only need to support running `wc FILE_NAME` and running `wc` (which should read data from standard input).

While you are working on this take the time to get some experience with `gdb`. Use it to step through your code and examine variables.

#### 3.3 Executables and addresses

Now that you have dusted off your C skills and gained some familiarity with the CS 162 tools, we want you to understand what is really inside of a running program and what the operating system needs to deal with.

Load up your `wc` executable in `gdb` with a single input file command line argument, set a breakpoint at `main`, start your program, and continue one line at a time until you are in the middle of your program's execution. Take a look at the stack using `where` or `backtrace` (`bt`).

While you are looking through `gdb`, think about the following questions and put your answers in the file `gdb.txt`.

- What is the value of `argv`? (hint: `print argv`)
- What is pointed to by `argv`? (hint: `print argv[0]`)
- What is the address of the function `main`?
- Try `info stack`. Explain what you see.
- Try `info frame`. Explain what you see.
- Try `info registers`. Which registers are holding aspects of the program that you recognize?

There is more to the executable than meets the eye. Let's look down inside. Run the following:

```
objdump -x -d wc
```

You will see that your program has several segments, names of functions and variables in your program correspond to labels with addresses or values. And the guts of everything is chunks of stuff within segments.

While you are looking through the `objdump` try and think about the following questions and put the answers in the file `objdump.txt`.



- What file format is used for this binary? And what architecture is it compiled for?
- What are some of the names of segments you find?
- What segment contains `main` (the function) and what is the address of `main`? (It should be the same as what you saw in `gdb`)
- Do you see the stack segment anywhere? What about the heap? Explain.

OK, now you are ready to write a program that reveals its own executing structure. The second file in `hw0`, `map.c` provides a rather complete skeleton. You will need to modify it to get the addresses that you are looking for. The output of the solution looks like the following (the addresses may be different).

```
_main @ 0x4005c2
recur @ 0x40057d
_main stack: 0x7ffffda11f73c
static data: 0x601048
Heap: malloc 1: 0x671010
Heap: malloc 2: 0x671080
recur call 3: stack@ 0x7ffffda11f6fc
recur call 2: stack@ 0x7ffffda11f6cc
recur call 1: stack@ 0x7ffffda11f69c
recur call 0: stack@ 0x7ffffda11f66c
```

Now think about the following questions and put the answers in `map.txt`.

- Using `objdump` with the `-D` flag on the `map` executable. Which of the addresses from the output of running `./map` are defined in the executable, and which segment is each defined in?
- Make a list of the important segments, and what they are used for (look up their names on the Internet if you don't know).
- What direction is the stack growing in?
- How large is the stack frame for each recursive call?
- Where is the heap? What direction is it growing in?
- Are the two `malloc()`ed memory areas contiguous? (e.g. is there any extra space between their addresses?)

### 3.4 user limits

The operating system needs to deal with the size of the dynamically allocated segments: the stack and heap. How large should these be? Poke around a bit to find out how to get and set these limits on linux. Modify `main.c` so that it prints out the maximum stack size, the maximum number of processes, and maximum number of file descriptors. Currently, when you compile and run `main.c` you will see it print out a bunch of system resource limits (stack size, heap size, ..etc). Unfortunately all the values will be 0! Your job is to get this to print the ACTUAL limits (use the soft limits, not the hard limits). (Hint: `man getrlimit`)

You should expect output similar to this:

```
stack size: 8388608
process limit: 2782
max file descriptors: 1024
```

### 3.5 Autograder & Submission

To push to autograder do:

```
cd ~/code/personal/hw0
git status
git add wc.c main.c map.c gdb.txt objdump.txt map.txt Makefile
git commit -m "Finished my first CS162 assignment"
git push personal master
```

This saves your work and it gives the instructors a chance to see the progress you are making. Congratulations for not waiting till the last minute.

Within a few minutes you should receive an email from the autograder. (If not, please notify the instructors via Piazza). Check [cs162.eecs.berkeley.edu/autograder](https://cs162.eecs.berkeley.edu/autograder)<sup>20</sup> for more information.

Hopefully after this you are slightly more comfortable with your tools. You will need them for the long road ahead!

---

<sup>20</sup><https://cs162.eecs.berkeley.edu/autograder>